

## PLASBLAK® LL2590



### Black Polyethylene Masterbatch for Cold Potable Water Pipe and Cable Sheathing Applications

PLASBLAK LL2590 is designed for use in cold potable water pipe and cable sheathing applications. It contains a small particle size carbon black together with an antioxidant approved for use in potable water which offer maximum protection against UV light degradation.

This product is suitable for use in a wide range of plastics that come into contact with food. For more details regarding the food contact compliance in various European countries, please refer to the relevant Food Contact Statement that you can obtain through your usual Cabot representative.

#### Method of Addition

PLASBLAK LL2590 is designed for ease of dilution and homogeneous mixing and is therefore suitable for direct addition using automatic dosing units or by pre-blending.

#### Addition Rate

The amount of masterbatch added depends on the performance requirements of the final application. The recommended addition rate for maximum UV light protection is 6.25% masterbatch.

#### Physical Properties

PROPERTY	VALUE	TEST METHOD (*)
Carrier	LLDPE	-
Pigment	40% P-type carbon black	-
Additive	Antioxidant	-
Compatibility	LDPE, LLDPE, HDPE, PP	-
Density @ 23°C	1140 kg/m <sup>3</sup>	CTM E023
MFI 21,6 kg/190°C	7 g/10 min	CTM E005 (ISO 1133)

(\*) Tests are performed according to Cabot Test Methods (CTM) based on international standards.

Quoted test results should not be used for specification purposes but are typical test values intended for guidance only.

# PLASBLAK® LL2590

## Packaging

PLASBLAK LL2590 is supplied in regular pellet form packed in 25 kg bags. It should be stored in a dry place.

Recommended storage life: up to 1 year provided it is stored as directed.



[cabotcorp.com](http://cabotcorp.com)

### NORTH AMERICA

Cabot Corporation Business  
and Technical Center  
157 Concord Road  
Billerica, MA 01821-7001  
USA

**TEL** +1 800 462 2313  
**FAX** +1 978 670 7035

### SOUTH AMERICA

Cabot Latin American  
Division  
Rue do Paraíso, 148 -  
5º andar  
04103-000, Sao Paulo,  
SP BRAZIL

**TEL** +55 11 2144 6400  
**FAX** +55 11 3253 0051

### EUROPE

Cabot Specialty Chemicals  
Interleuvenlaan 15 i  
3001 Leuven,  
BELGIUM

**TEL** +32 16 39 24 31  
**TEL** +32 16 39 25 68  
**FAX** +32 16 39 24 44

### MIDDLE EAST/AFRICA

Cabot Specialty Chemicals  
Jebel Ali Free Zone  
LOB 15, Office 424  
Dubai

UNITED ARAB EMIRATES  
**TEL** +971 4 8871 800  
**FAX** +971 4 8871 801

### ASIA PACIFIC

Cabot China Ltd.  
558 Shuangbai Road  
Shanghai 201108,  
CHINA

**TEL** +86 21 5175 8800  
**FAX** +86 21 6434 5532

### JAPAN

Cabot Specialty Chemicals, Inc.  
Sumitomo Chiba-Daimon Idg. 3F  
2-5-5 Shiba Daimon,  
Minato-ku, Tokyo 105-0012,  
JAPAN

**TEL** +81 3 6820 0255  
**FAX** +81 3 5425 4500

This information is provided as a convenience and for informational purposes only. No guarantee or warranty as to this information, or any product to which it relates, is given or implied. This information may contain inaccuracies, errors or omissions and CABOT DISCLAIMS ALL WARRANTIES EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE AS TO (i) SUCH INFORMATION, (ii) ANY PRODUCT OR (iii) INTELLECTUAL PROPERTY INFRINGEMENT. In no event is Cabot responsible for, and Cabot does not accept and hereby disclaims liability for, any damages whatsoever in connection with the use of or reliance on this information or any product to which it relates.