

PLASBLAK® LL4897 BLACK MASTERBATCH

Product highlights

PLASBLAK LL4897 black masterbatch has been developed for use in silage stretch wrap film applications. The masterbatch contains a carefully selected carbon black together with an antioxidant package to enable the masterbatch with excellent weathering performance for silage stretch wrap film during its service life.

This product is suitable for use in a wide range of plastics that come into contact with food. For more details regarding the food contact compliance in various European countries, please refer to the relevant Food Contact Statement that you can obtain through your Cabot representative.



Method of addition

PLASBLAK LL4897 black masterbatch is designed for ease of dilution and homogeneous mixing and is therefore suitable for direct addition using automatic dosing units or by pre-blending.

Addition rate

The amount of masterbatch added depends on the performance requirements of the final application. The typical addition level for enhanced UV protection is 6.25% masterbatch. For optimal weathering performance in hotter climates, the addition of further UV stabilizers in the silage film manufacturing process may be required.

TYPICAL PROPERTIES

PROPERTY	TYPICAL VALUE	UNITS	TEST METHOD
Carrier	Polyethylene	-	-
Pigment	40% carbon black	-	-
Additive	Antioxidant	-	-
Compatibility	LDPE, LLDPE, HDPE, PP	-	-
Density @ 23°C	1150	kg/m ³	ISO 1183
MFI 190°C/10 kg	4	g/10 min	ISO 1133

The data in the table above are typical test values intended as guidance only, and are not product specifications. Product specifications are available from your Cabot representative.

PLASBLAK® LL4897 BLACK MASTERBATCH

Products form and logistics

- ◆ Product form: pellets
- ◆ Regional availability: global
- ◆ Packaging options: 25kg bags

For information on product-specific storage conditions, please refer to the applicable Safety Data Sheet (SDS) available from your Cabot representative or at cabotcorp.com.

The PLASBLAK name is a registered trademark of Cabot Corporation.

NORTH AMERICA

Cabot Plastics Canada
707 Pierre Tremblay Boulevard
Saint-Jean-sur-Richelieu
QC, J2X 5G5
Canada
T +1 450 347 4371
F +1 450 347 9936

SOUTH AMERICA

Cabot Brasil Industria e
Comercio Ltda.
Rua do Paraíso 148 - 5º andar
04103-000 São Paulo
Brazil
T +55 11 2144 6400
F +55 11 3253 0051

EUROPE

SIA Cabot Latvia
74A Gustava Zemgala gatve
LV- 1039 Riga
Latvia
T +371 670 50 900
F +371 670 50 985

MIDDLE EAST/AFRICA

Cabot Specialty Chemicals
Jebel Ali Free Zone
LOB 15, Office 424, Dubai
United Arab Emirates
T +971 4 8871 800
F +971 4 8871 801

ASIA PACIFIC

Cabot China Ltd.
558 Shuangbai Road
Minghang District
Shanghai 201108
China
T +86 21 5175 8800
F +86 21 6434 5532

JAPAN

Cabot Specialty Chemicals, Inc.
Sumitomo Chiba-Daimon Bldg, 3F
2-5-5 Shiba Daimon,
Minato-ku, Tokyo 105-0012
Japan
T +81 6820 0255
F +81 3 5425 4500

The data and conclusions contained herein are based on work believed to be reliable, however, Cabot cannot and does not guarantee that similar results and/or conclusions will be obtained by others. This information is provided as a convenience and for informational purposes only. No guarantee or warranty as to this information, or any product to which it relates, is given or implied. This information may contain inaccuracies, errors or omissions and CABOT DISCLAIMS ALL WARRANTIES EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE AS TO (i) SUCH INFORMATION, (ii) ANY PRODUCT OR (iii) INTELLECTUAL PROPERTY INFRINGEMENT. In no event is Cabot responsible for, and Cabot does not accept and hereby disclaims liability for, any damages whatsoever in connection with the use of or reliance on this information or any product to which it relates.