



# SAFETY DATA SHEET

Prepared in accordance with the United States Hazard Communication Standard: 29 CFR 1910.1200 (2012)

Revision date: 31-Jul-2015

## 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product name: ThermalWrap™ TW350

Product code: TW350

Synonyms: None

Recommended use: Various, Insulating material, Industrial Products, Absorbant

Restrictions on use: Not Applicable.

Supplier:

Cabot Corporation 4400 North Point Parkway Suite 200 Alpharetta, Georgia 30022 United States Tel: +1 678 297 1300	Cabot Corporation 157 Concord Road Billerica, MA 01821 UNITED STATES Tel: 1-978-663-3455 Fax: 1-978-670-6955
----------------------------------------------------------------------------------------------------------------------------------	-----------------------------------------------------------------------------------------------------------------------------

Emergency Telephone Number: 24H/7d service  
Canada: CANUTEC 1-613-996-6666  
US: CHEMTREC 1-800-424-9300 or 1-703-527-3887  
Germany: CHEMTREC 0800-181-7059  
International CHEMTREC: +1 703-741-5970 or +1-703-527-3887

## 2. HAZARDS IDENTIFICATION

### Classification

OSHA Regulatory Status: This chemical is not considered hazardous by the United States 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200).

### Label Elements:

Pictogram: None  
Signal Word: None  
Hazard statements: None

Precautionary Statements: None

Hazards not otherwise classified (HNOC)

Do not expose to temperatures above 125°C. Hazardous products of combustion can include carbon monoxide, carbon dioxide and formaldehyde. Organic products of decomposition.

Potential health effects

Principle Routes of Exposure: Skin Contact, Eye contact, Inhalation

Eye Contact: May cause mechanical irritation. Avoid contact with eyes.

Skin Contact: May cause mechanical irritation and skin drying. Avoid contact with skin. No cases of sensitization in humans have been reported.

Inhalation: Dust may be irritating to respiratory tract. Provide appropriate exhaust ventilation at machinery and at places where dust can be generated. See also Section 8.

Ingestion: Adverse health effects are not expected. See Section 11.

Carcinogenicity: Does not contain any substances greater than 0.1% listed by IARC (International Agency for Research on Cancer), NTP (National Toxicology Program), OSHA (Occupational Safety and Health Administration), ACGIH (American Conference for Governmental Industrial Hygienists) or EU (European Union). See also Section 11.

Target Organ Effects: Skin, Lungs, See Section 11

Medical Conditions Aggravated by Exposure: Asthma, Respiratory disorder, Skin disorders

Potential Environmental Effects: None known. See Section 12.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Synonyms: None.

Chemical name	CAS No	weight-%	Trade secret
Silica, [(trimethylsilyl)oxy]-modified	102262-30-6	45-85	-
Copolyolefin bicomponent fiber		15-55	-

Other Information:

The hyphen (-) means "not applicable"

### 4. FIRST AID MEASURES

FIRST AID MEASURES

Skin Contact Wash thoroughly with soap and water. Seek medical attention if symptoms develop.

Eye contact Flush eyes immediately with large amounts of water for 15 minutes. Seek medical attention if symptoms develop.

Inhalation If cough, shortness of breath or other breathing problems occur, move to fresh air. Seek medical attention if symptoms persist. If necessary, restore normal breathing through standard first aid measures.

Ingestion Do not induce vomiting. If conscious, give several glasses of water. Never give anything by mouth to an unconscious person.

#### Most important symptoms and effects, both acute and delayed

Symptoms: The most important known symptoms and effects are described in Section 2 and/or in Section 11.

#### Indication of any immediate medical attention and special treatment needed

Note to physicians: Treat symptomatically.

### 5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Carbon dioxide (CO<sub>2</sub>). Foam. Dry chemical. Water.

Unsuitable Extinguishing Media: None.

Specific hazards arising from the chemical: May release formaldehyde when heated to high temperatures in the presence of air. Formaldehyde is a known skin and lung sensitizer and is regulated as a carcinogen.

Polyesters can burn if exposed to flame, releasing toxic and/or flammable fumes and vapors.

Hazardous combustion products: Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>). Formaldehyde. Organic products of decomposition.

Protective equipment and precautions for firefighters: In the event of fire, wear self-contained breathing apparatus. Wear suitable protective equipment.

Risk of Dust Explosion: Not Applicable Will not cause dust explosion

### 6. ACCIDENTAL RELEASE MEASURES

#### Personal precautions, protective equipment and emergency procedures

Personal precautions: Avoid dust formation. Ensure adequate ventilation. Use personal protective equipment. See also Section 8.

For emergency responders: Use personal protection recommended in Section 8.

#### Environmental Precautions:

Environmental Precautions: Contain spilled product on land, if possible. Local authorities should be advised if significant spillages cannot be contained.

#### Methods and material for containment and cleaning up

Methods for containment: Prevent further leakage or spillage if safe to do so.

---

Methods for cleaning up: Clean up promptly by vacuum. Use of a vacuum with high efficiency particulate air (HEPA) filtration is recommended. Do not create a dust cloud by using a brush or compressed air. Dry sweeping is not recommended. See Section 13.

## 7. HANDLING AND STORAGE

### Precautions for safe handling

Advice on safe handling: Avoid contact with skin and eyes. Avoid dust formation. Do not breathe dust. Provide appropriate exhaust ventilation at machinery and at places where dust can be generated. Do not create a dust cloud by using a brush or compressed air.

General hygiene considerations: Handle in accordance with good industrial hygiene and safety practice

### Conditions for safe storage, including any incompatibilities

Storage Conditions: Keep in properly labeled containers. Keep containers tightly closed in a dry and well-ventilated place. Store at ambient conditions.

Incompatible materials: None known.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure guidelines: There are no exposure limits identified for this product. Exposure limits for components or similar components are stated below. The table below is a summary. Please see the specific legislation for complete information.

Amorphous Silica, The regulatory exposure limits are found under the general silica, CAS RN 7631-86-9:	Australia:	2 mg/m <sup>3</sup> , TWA, Respirable
	Austria MAK	4 mg/m <sup>3</sup> , TWA, Inhalable fraction
	Finland:	5 mg/m <sup>3</sup>
	Germany TRGS 900:	4 mg/m <sup>3</sup> , TWA, Inhalable fraction
	India:	10 mg/m <sup>3</sup> , TWA
	Ireland:	2.4 mg/m <sup>3</sup> , TWA, Respirable dust
	Norway:	1.5 mg/m <sup>3</sup> , TWA, Respirable dust
	Switzerland:	4 mg/m <sup>3</sup> , TWA
	UK WEL:	6 mg/m <sup>3</sup> , TWA, Inhalable fraction
	US OSHA PEL:	2.4 mg/m <sup>3</sup> , TWA, Respirable fraction
		6mg/m <sup>3</sup> (54 FR2701)

---

Dust, or Particulates Not Otherwise Specified:	Belgium:	10 mg/m <sup>3</sup> , TWA, Inhalable 3 mg/m <sup>3</sup> TWA, Respirable
	China:	8 mg/m <sup>3</sup> , TWA 10 mg/m <sup>3</sup> , STEL
	France:	10 mg/m <sup>3</sup> , TWA Inhalable dust 5 mg/m <sup>3</sup> , TWA Respirable dust
	Italy:	10 mg/m <sup>3</sup> , TWA, Inhalable 3 mg/m <sup>3</sup> , TWA, Respirable
	Malaysia:	10 mg/m <sup>3</sup> , TWA, Inhalable 3 mg/m <sup>3</sup> , TWA, Respirable
	Spain:	10 mg/m <sup>3</sup> , VLA, Inhalable 3 mg/m <sup>3</sup> , VLA, Respirable
	US ACGIH - PNOS:	10 mg/m <sup>3</sup> , TWA, Inhalable 3 mg/m <sup>3</sup> , TWA, Respirable
	US OSHA - PEL:	15 mg/m <sup>3</sup> , TWA, Total dust 5 mg/m <sup>3</sup> , TWA, Respirable

**NOTE:**

In its facilities globally, Cabot Corporation manages silica to the Germany TRGS 900 occupational exposure limit of 4 mg/m<sup>3</sup>, TWA, Inhalable fraction

MAK: Maximale Arbeitsplatzkonzentration (Maximum Workplace Concentration)

PEL: Permissible Exposure Limit

PNOS: Particulate Not Otherwise Specified

STEL: Short Term Exposure Limit

TRGS: Technische Regeln für Gefahrstoffe (Technical Rule for Hazardous Materials)

TWA: Time Weighted Average

US ACGIH: United States American Conference of Governmental Industrial Hygienists

US OSHA: United States Occupational Safety and Health Administration

VLA: Valore Limite Ambientales (Environmental Limit Value)

WEL: Workplace Exposure Limit

**Engineering Controls:** Ensure adequate ventilation to maintain exposures below occupational limits. Provide appropriate local exhaust ventilation at machinery and at places where dust can be generated.

Personal protective equipment [PPE]

**Respiratory Protection:** Approved respirator may be necessary if local exhaust ventilation is not adequate.

**Hand Protection:** Wear protective gloves to prevent skin drying. Use protective barrier cream before handling the product. Wash hands and other exposed skin with mild soap and water.

**Eye/face Protection:** Wear eye/face protection. Wear safety glasses with side shields (or goggles).

**Skin and Body Protection:** Wear suitable protective clothing. Wash clothing daily. Work clothing should not be allowed out of the workplace.

Other: Handle in accordance with good industrial hygiene and safety practice. Emergency eyewash and safety shower should be located nearby.

Environmental exposure controls: In accordance with all local legislation and permit requirements as applicable for dusts.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State:	Solid	Odor:	None.
Appearance:	Flexible blanket	Odor threshold:	No information available
Color:	White		

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH:		No information available
Melting point/freezing point:	1700	Fiber core melts at about 256°C and the sheaths at various temperatures from 110°C to 150°C (copolyolefin bicomponent fiber)
Boiling point / boiling range:		Not Applicable
Evaporation Rate:		Not Applicable
Vapor pressure:		Not Applicable
Vapor Density:		Not Applicable
Density:	50 - 100 kg/m <sup>3</sup>	No information available
Bulk Density:		Not Applicable
Specific Gravity at 20°C:		No information available
Water solubility:		No information available
Solubility(ies):		No information available
Partition Coefficient (n-octanol/water):		Not Applicable
Decomposition temperature:	> 125 °C	
Viscosity:		Not Applicable
Kinematic viscosity:		Not Applicable
Dynamic viscosity:		Not Applicable
Oxidizing Properties:		No oxidizing properties
Softening point:		No information available
VOC content (%):		Negligible
% Volatile (by Volume):		No information available
% Volatile (by Weight):		No information available
Surface Tension:		Not Applicable
Explosive properties:		Non-explosible
Flash Point:		Not Applicable
Flammability (solid, gas):		No information available
Flammability Limit in Air:		
Explosion Limits in Air - Upper (g/m <sup>3</sup> ):		Not Applicable
Explosion Limits in Air - Lower (g/m <sup>3</sup> ):		Not Applicable
Autoignition Temperature:		No information available
Minimum Ignition Temperature:		No information available
Minimum Ignition Energy:		No information available
Ignition Energy:		No information available

Maximum Absolute Explosion Pressure:	Not Applicable
Maximum Rate of Pressure Rise:	Not Applicable
Burn Velocity:	No information available
Kst Value:	Not Applicable
Dust Explosion Classification:	Not Applicable

End point is listed "not applicable" due to the inherent properties of the substance  
"No information available" indicates testing has not been performed

## 10. STABILITY AND REACTIVITY

Reactivity:	Not reactive.
Stability:	Stable under recommended handling and storage conditions.
Possibility of hazardous reactions:	None under normal processing.
Hazardous polymerization:	Hazardous polymerization does not occur.
Conditions to avoid:	Polyesters can burn if exposed to flame, releasing toxic and/or flammable fumes and vapors. Fiber core melts at about 256°C and the sheaths melt at various temperatures from 110°C to 150°C (copolyolefin bicomponent fiber). Heating above 300°C leads to decomposition of Aerogel surface treatment. Decomposition vapor should be ventilated. May release formaldehyde when heated to high temperatures in the presence of air. Formaldehyde is a known skin and lung sensitizer and is regulated as a carcinogen.
Incompatible materials:	None known.
Explosion data	See also Section 9.
Sensitivity to Mechanical Impact:	None.
Sensitivity to Static Discharge:	This material will not create nor support conditions that would result in a dust explosion or fire. Take precautionary measures against static discharges. Avoid dust formation. All metal parts of the mixing and processing equipment must be earthed/grounded. Ensure all equipment is electrically earthed/grounded before beginning transfer operations.
Hazardous decomposition products:	Carbon monoxide (CO). Carbon dioxide (CO <sub>2</sub> ). Formaldehyde. Organic products of decomposition.

## 11. TOXICOLOGICAL INFORMATION

*Product, as formulated, has not been tested. Information given is based on data on the components and the toxicology of similar products: Synthetic Amorphous Silica, Treated Synthetic Amorphous Silica.*

### Acute toxicity

Oral LD50:	LD50/oral/rat = > 5000 mg/kg. No deaths occurred and no signs of toxicity were seen during the observation periods after single oral administration of the substance. (OECD 423).
Inhalation LC50:	Due to the product's physical characteristics, no suitable testing procedure is available

---

Dermal LD50:	No data are available on the product itself.  Synthetic Amorphous Silica. LD50/dermal/rabbit = > 2000 mg/kg. Very slight transient erythema in one animal. No signs of systemic or organ toxicity (OECD 402).
Skin corrosion/irritation:	Primary irritation index = 0.0 @ 24 hr. Not classified as an irritant (OECD 404)
Serious eye damage/eye irritation:	Not classified as an irritant in rabbit studies (OECD 405). High dust concentrations may cause mechanical irritation.
Sensitization:	Non-sensitizing. A delayed contact hypersensitivity study in guinea pigs utilizing the Buehler technique was performed.
Mutagenicity:	Not mutagenic in Ames test. Negative in the chromosome aberration test in Chinese hamster ovary (CHO) cells.
Carcinogenicity:	No data are available on the product itself.  Synthetic Amorphous Silica. No evidence of carcinogenicity was observed in multiple animal species following repeated oral or inhalation exposure to amorphous silica. Similarly, epidemiology studies show no evidence of carcinogenicity in workers who manufacture amorphous silica.
Reproductive and Developmental Toxicity:	No effects on reproductive organs or fetal development have been reported in animal toxicity studies.
STOT - single exposure:	Specific target organ toxicity is not expected after single oral, single inhalation, or single dermal exposure.
STOT - repeated exposure:	No data are available on the product itself.  Treated Synthetic Amorphous Silica: Repeated dose toxicity: oral (rat), 28-d, diet, no significant treatment-related adverse effects at the doses tested. Derived No Adverse Effects Level (NOAEL) in the range of 1000 mg/kg/d.  Synthetic Amorphous Silica: Repeated dose toxicity: oral (rat), 2 weeks to 6 months, no significant treatment-related adverse effects at doses of up to 8% silica in the diet. Repeated dose toxicity: inhalation (rat), 13 weeks, Lowest Observed Effect Level (LOEL) = 1.3 mg/m <sup>3</sup> based on mild reversible effects in the lungs. Repeated dose toxicity: inhalation (rat), 90 days, LOEL = 1 mg/m <sup>3</sup> based on reversible effects in the lungs and effects in the nasal cavity.  Based on available data, a STOT-RE classification is not warranted.
Aspiration Hazard:	Based on industrial experience and available data, no aspiration hazard is expected.

## 12. ECOLOGICAL INFORMATION



Aquatic Toxicity: No data are available on the product itself  
Aquatic toxicity is unlikely due to low solubility

Synthetic Amorphous Silica  
Fish (Brachydanio rerio) LC50 (96 h): > 10,000 mg/l; (Method: OECD 203)  
No acute toxicity to Daphnia with EL and EL<sub>50</sub> ranging from >1000 to 10,000 mg/L (OECD 202)

#### ENVIRONMENTAL FATE

Persistence and degradability The methods for determining biodegradability are not applicable to inorganic substances

Bioaccumulation Not expected due to physicochemical properties of the substance.

Mobility: Not expected to migrate.

Distribution to Environmental Compartments: No information available.

Other adverse effects: No information available.

### 13. DISPOSAL CONSIDERATIONS

Disclaimer: Information in this section pertains to the product as shipped in its intended composition as described in Section 3 of this MSDS. Contamination or processing may change waste characteristics and requirements. Regulations may also apply to empty containers, liners or rinsate. State/provincial and local regulations may be different from federal regulations. The person generating waste must determine its proper classification

Unused and Uncontaminated Product: Product, as supplied, should be disposed of in accordance with the regulations issued by the appropriate federal, state and local authorities. Same consideration should be given to containers and packaging.

### 14. TRANSPORT INFORMATION

#### DOT

UN/ID no	Not regulated
Proper Shipping Name	Not regulated
Hazard Class	Not regulated
Packing group	Not regulated

#### ICAO (air)

UN/ID no	Not regulated
Proper Shipping Name	Not regulated
Hazard Class	Not regulated
Packing group	Not regulated

IATA

UN/ID no	Not regulated
Proper Shipping Name	Not regulated
Hazard Class	Not regulated
Packing group	Not regulated

IMDG

UN/ID no	Not regulated
Proper Shipping Name	Not regulated
Hazard Class	Not regulated
Packing group	Not regulated

RID

UN/ID no	Not regulated
Proper Shipping Name	Not regulated
Hazard Class	Not regulated
Packing group	Not regulated

ADR

UN/ID no	Not regulated
Proper Shipping Name	Not regulated
Hazard Class	Not regulated
Packing group	Not regulated

15. REGULATORY INFORMATION
----------------------------

*Hazard Classification*

United States - OSHA (29 CFR 1910.1200): Not Hazardous

Canada - WHMIS Classification (CPR, SOR/88-66): Not controlled

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the M/SDS contains all the information required by the Controlled Products Regulations.

*International Inventories*

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory	Complies
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List	Complies
EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances	Complies
ENCS - Japan Existing and New Chemical Substances	Complies
IECSC - China Inventory of Existing Chemical Substances	Complies
KECL - Korean Existing and Evaluated Chemical Substances	Complies
PICCS - Philippines Inventory of Chemicals and Chemical Substances	Complies
AICS - Australian Inventory of Chemical Substances	Complies
NZIoC - New Zealand Inventory of Chemicals	Complies
TCSI - Taiwan Chemical Substance Inventory	Complies

*US Federal Regulations*

TSCA Section 12(b) Export Regulations:

This product does not contain any chemicals which require export notification under TSCA 12(b).

SARA 311/312 Hazard Categories

Acute Health Hazard	NO
Chronic Health Hazard	NO
Fire hazard	NO
Sudden release of pressure hazard	NO
Reactive Hazard	NO

Clean Air Act Amendments of 1990

(CAA, Section 112, 40 CFR 82):

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

*US State Regulations*California Proposition 65

This product does not contain any Proposition 65 chemicals.

*U.S. State Right-to-Know Regulations*

This product contains a listed component(s) on the Massachusetts Right-to-Know Substances List. New Jersey Right-to-Know List. Pennsylvania Right-to-Know List.: Silica (CAS# 7631-86-9).

16. OTHER INFORMATION
-----------------------

Pharmaceutical Use:

Not permitted

Food Additive Use:

Not permitted

Contacts:

*Manufacturing Site*

Cabot Aerogel GmbH  
Industriepark Hoechst D660  
65926 Frankfurt am Main  
GERMANY  
Tel: (+49) 69-305-22102  
Fax: (+49) 69-305-22103

Disclaimer:

The information set forth is based on information that Cabot Corporation believes to be accurate. No warranty, expressed or implied, is intended. The information is provided solely for your information and consideration and Cabot assumes no legal responsibility for use or reliance thereon. In the event of a discrepancy between the information on the non-English document and its English counterpart, the English version shall supersede.

Prepared by: Cabot Corporation - Safety, Health and Environmental Affairs  
Revision date: 31-Jul-2015

® and 'TM' indicate trademarks of the Cabot Corporation.

End of Safety Data Sheet